



Pump Motors

NEMA

MOTOR MODEL:	BK3-CI-TF-444T-6-RR-G-100
FACTORY TYPE:	-

NEMA Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	100.0	-
Speed, RPM	1138	-
Voltage	230/460/796	-
# Phase	-	
Full Load Amps	223.6/111.8/64.6	-
Power Factor	0.91	3.0
Nominal Efficiency	92.5	-
3/4 Load Efficiency	-	-
Service Factor	1.15	-
KVA Code	F	-
FL Amps. @ 208 V	-	-
Locked Rotor Current	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	12	
Connection	-	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	-	-
75%	93.2	-
100%	92.5	0.91
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	-	-
3D Image Link		
Not available for this motor		

GENERAL DATA		
Frame Size	444T	
Frame Enclosure	TEFC	
Mounting	Rigid	
Insulation Class	F	
Duty	-	
NEMA Design	D	
Frame Material	Cast Iron	
Ingress Protection	55	
Tropicalization	-	
Cable Entry	-	
Feet Removable	-	
Double Drilled	-	
Paint Color	-	
Paint RAL	-	
Weight lb	1602.0	
MECHANICAL DATA		
DE Bearing	NU6319	
NDE Bearing	6319C3	
dB No-Load	-	
Rotor Wk ² , Lb-Ft ²	-	
Comp Ring (wavey washer)	-	
TORQUE VALUES	Torque lb-ft	% FLT
Locked Rotor Torque	-	-
Pull-Up Torque	-	-
Breakdown Torque	-	-
Full Load Torque	-	-
SITE CONDITIONS		
Ambient Temp °C	-	
Altitude Above Sea Level m	-	



Pump Motors

NEMA

MOTOR MODEL:	BK3-CI-TF-444T-6-RR-G-100
FACTORY TYPE:	-

NEMA Cast Iron, TEFC

Non Sinusoidal (VFD) Output 100.0HP, 1138 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	-	-	Start Configuration
Pull-Up Torque	-	-	Starting Current (A)
Breakdown Torque	-	-	No-Load Current (A)
Full Load	-	-	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	93.2	-
100	-	-	-	-	92.5	0.91
125	-	-	-	-	-	-

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com