



EPAct

**NEMA**

<b>MOTOR MODEL:</b>	BL3-AL-TF-56C-4-B-D-1.5
<b>FACTORY TYPE:</b>	TFA

## EPAct NEMA Cast Aluminum, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	1.5	1.5
Speed, RPM	1725	-
Voltage	208-230/460	-
# Phase	3	-
Full Load Amps	4.65-4.5/2.25	-
Power Factor	0.75	-
Nominal Efficiency	82.0	-
3/4 Load Efficiency	-	-
Service Factor	1.15	-
KVA Code	H	-
FL Amps. @ 208 V	4.65	-
Locked Rotor Current	-	-
Start Capacitor	-	-
Start Capacitor V	-	-
Run Capacitor	-	-
Run Capacitor V	-	-
Number of Leads	9	-
Connection	YY/Y	-
Coil Resistance	-	-
Date Code	-	-
Load	Efficiency %	P.F.
50%	-	-
75%	-	-
100%	-	-
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	-	-
3D Image Link		
Not available for this motor		

GENERAL DATA			
Frame Size	56C		
Frame Enclosure	TEFC		
Mounting	Rigid/C-Flange		
Insulation Class	F		
Duty	Cont. / S1		
NEMA Design	B		
Frame Material	Cast Aluminum		
Ingress Protection	55		
Tropicalization	true		
Cable Entry	1-NPT 1/2"		
Feet Removable	true		
Double Drilled	-		
Paint Color	Graphite Gray		
Paint RAL	7024		
Weight lb	26.0		
MECHANICAL DATA			
DE Bearing	6204ZZ		
NDE Bearing	6204ZZ		
dB No-Load	-		
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	-		
Comp Ring (wavey washer)	NDE		
TORQUE VALUES		Torque lb-ft	% FLT
Locked Rotor Torque		-	-
Pull-Up Torque		-	-
Breakdown Torque		-	-
Full Load Torque		-	-
SITE CONDITIONS			
Ambient Temp °C		40	
Altitude Above Sea Level m		1000	

\*This report valid for above Date Code and newer models, please contact Techtop for more info.



EPAct

**NEMA**

<b>MOTOR MODEL:</b>	BL3-AL-TF-56C-4-B-D-1.5
<b>FACTORY TYPE:</b>	TFA

EPAct NEMA Cast Aluminum, TEFC

Non Sinusoidal (VFD) Output 1.5HP, 1725 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	-	-	Start Configuration
Pull-Up Torque	-	-	Starting Current (A)
Breakdown Torque	-	-	No-Load Current (A)
Full Load	-	-	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-