

Techtop Industries Nameplate and Performance Data

NAMEPLATE DATA		
	60 Hz.	50 Hz.
Horsepower	-	-
Frame Size	-	-
Speed, RPM	-	-
Voltage	3 Phase US	-
# Phase	-	-
Full Load Amps	-	-
Power Factor	-	-
Nominal Efficiency	-	-
3/4 Load Efficiency	-	-
Service Factor	-	-
Duty	-	-
FL Temp Rise °C	-	-
Enclosure	-	-
Ambient Temp °C	-	-
KVA Code	-	-
FL Amps. @ 208 V	-	-
Insulation Class	-	-
NEMA Design	-	-
Weight	-	-
DE Bearing	-	-
NDE Bearing	-	-
dB No-Load	-	-
Rotor Wk ² , Lb-Ft ²	-	-
Start Capacitor		
Start Capacitor V		
Run Capacitor		
Run Capacitor V		
Number of Leads	-	-
Connection	-	-
Coil Resistance	-	-

Motor Model:	BL3-RS-OP-56H-4-B-D-.75-RS
---------------------	-----------------------------------

Performance Load Values:

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-
150	-	-	-	-	-	-
SF	-	-	-	-	-	-

	Torque, Lb-Ft	% Full Load Torque	Speed, RPM	Current Amps.
Locked Rotor Torque	-	-	-	-
Pull Up Torque	-	-	-	-
Breakdown Torque	-	-	-	-
Full Load	-	-	-	-

Speed Torque Curve

Please contact Techtop for image.

Dimensional Drawing

Please contact Techtop for image.

Dimensions are for reference only. Allowance should be made for minor deviations in non standard specified properties.

3D Image Link: Not available for this motor