



NEMA Premium

NEMA

MOTOR MODEL:	BR3-CI-TF-365TS-2-BR-E-75
FACTORY TYPE:	TXC

Premium NEMA Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	75.0	75.0
Speed, RPM	3560	2940
Voltage	460	380
# Phase	3	
Full Load Amps	84.3	101.5
Power Factor	0.9	-
Nominal Efficiency	93.6	91.2
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
KVA Code	K	F
FL Amps. @ 208 V	-	-
LRC @ 60Hz HV	941.877	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	12	
Connection	DD/D	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	92.53	0.83
75%	93.68	0.89
100%	93.68	0.89
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	62.0	-
3D Image Link		
BR3-CI-TF-365TS-2-BR-E-75		

GENERAL DATA		
Frame Size	365TS	
Frame Enclosure	TEFC	
Mounting	Rigid	
Insulation Class	F	
Duty	Cont. / S1	
NEMA Design	A	
Frame Material	Cast Iron	
Ingress Protection	56	
Tropicalization	true	
Cable Entry	1-NPT 2"	
Feet Removable	-	
Double Drilled	true	
Paint Color	Graphite Gray	
Paint RAL	7024	
Weight lb	784.98	
MECHANICAL DATA		
DE Bearing	6313C3	
NDE Bearing	6313C3	
dB No-Load	-	
Rotor Wk ² , Lb-Ft ²	-	
Comp Ring (wavy washer)	DE	
TORQUE VALUES		
	Torque lb-ft	% FLT
Locked Rotor Torque	447.777	408.0
Pull-Up Torque	210.719	192.0
Breakdown Torque	409.365	373.0
Full Load Torque	109.749	100.0
SITE CONDITIONS		
Ambient Temp °C	40	
Altitude Above Sea Level m	1000	

*This report valid for above Date Code and newer models, please contact Techtop for more info.

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com




NEMA Premium

NEMA

MOTOR MODEL:	BR3-CI-TF-365TS-2-BR-E-75
FACTORY TYPE:	TXC

Premium NEMA Cast Iron, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	447.777	408.0	Start Configuration
Pull-Up Torque	210.719	192.0	Starting Current (A)
Breakdown Torque	409.365	373.0	No-Load Current (A)
Full Load	109.749	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	21.47	-	-	-	-
25	18.75	29.98	15.92	3593.2	87.92	0.67
50	37.5	45.56	30.26	3586.7	92.53	0.83
75	56.25	63.16	44.83	3579.8	93.68	0.89
100	75.0	63.16	44.83	3579.8	93.68	0.89
125	93.75	102.35	74.74	3565.1	93.66	0.92

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com