



NEMA Premium


NEMA

MOTOR MODEL:	BR3-CI-TF-404TC-6-RR-E-60
FACTORY TYPE:	TXC

Premium NEMA Cast Iron, TEFC

Non Sinusoidal (VFD) Output 60.0HP, 1185 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	636.28	237.0	Start Configuration
Pull-Up Torque	338.276	126.0	Starting Current (A)
Breakdown Torque	644.334	240.0	No-Load Current (A)
Full Load	268.473	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	24.92	-	-	-	-
25	15.0	29.93	12.66	1196.9	88.86	0.53
50	30.0	40.96	24.18	1193.9	93.05	0.74
75	45.0	54.47	35.88	1190.5	94.06	0.83
100	60.0	69.89	47.8	1186.9	94.14	0.86
125	75.0	79.81	55.06	1184.6	93.99	0.87

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com