



IE3

IEC

MOTOR MODEL:	GR3-AL-TF-132MB3-4-B-D-10
FACTORY TYPE:	TAX

IE3 IEC Cast Aluminum, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	10.0	10.0
Speed, RPM	1760	1455
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	23.9/12.0	28.0/14.0
Power Factor	0.86	-
Nominal Efficiency	91.7	-
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
KVA Code	L	J
FL Amps. @ 208 V	26.3	-
Locked Rotor Current	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	-	-
75%	-	-
100%	-	-
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	-	-
3D Image Link		
Not available for this motor		

GENERAL DATA			
Frame Size	132M		
Frame Enclosure	TEFC		
Mounting	B3		
Insulation Class	F		
Duty	Cont. / S1		
NEMA Design	-		
Frame Material	Cast Aluminum		
Ingress Protection	55		
Tropicalization	true		
Cable Entry	2-M25X1.5		
Feet Removable	true		
Double Drilled	-		
Paint Color	Graphite Gray		
Paint RAL	7024		
Weight lb	134.0		
MECHANICAL DATA			
DE Bearing	6308ZZ		
NDE Bearing	6208ZZ		
dB No-Load	-		
Rotor Wk ² , Lb-Ft ²	-		
Comp Ring (wavy washer)	NDE		
TORQUE VALUES		Torque lb-ft	% FLT
Locked Rotor Torque	-	-	
Pull-Up Torque	-	-	
Breakdown Torque	-	-	
Full Load Torque	-	-	
SITE CONDITIONS			
Ambient Temp °C	40		
Altitude Above Sea Level m	1000		

*This report valid for above Date Code and newer models, please contact Techttop for more info.

Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techttopind.com



IE3

IEC

MOTOR MODEL:	GR3-AL-TF-132MB3-4-B-D-10
FACTORY TYPE:	TAX

IE3 IEC Cast Aluminum, TEFC

Non Sinusoidal (VFD) Output 10.0HP, 1760 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	-	-	Start Configuration
Pull-Up Torque	-	-	Starting Current (A)
Breakdown Torque	-	-	No-Load Current (A)
Full Load	-	-	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-