

Techtop Industries Nameplate and Performance Data

NAMEPLATE DATA		
	60 Hz	50 Hz
Horsepower	0.5	0.5
Frame Size	56J	
Speed, RPM	3490	2870
Voltage	208-230/460	190/380
# Phase	3	
Full Load Amps	1.71-1.74/0.87	1.94/0.97
Power Factor	0.72	-
Nominal Efficiency	74.0	73.5
3/4 Load Efficiency	-	-
Service Factor	1.25	1.0
Duty	Cont. / S1	
FL Temp Rise °C	26.2	-
Enclosure	TEFC	
Ambient Temp °C	40	
KVA Code	L	H
FL Amps. @ 208 V	1.71	-
Insulation Class	F	
NEMA Design	B	
Weight	15.5	
DE Bearing	6204ZZ	
NDE Bearing	6204ZZ	
dB No-Load	-	
Rotor Wk ² , Lb-Ft ²	-	
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	-	

Motor Model:	GR3-AL-TF-56J-2-B-D-.5
---------------------	-------------------------------

Performance Load Values:

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	0.63	-	-	-	-
25	0.125	-	-	-	-	-
50	0.25	-	-	-	-	-
75	0.375	-	-	-	-	-
100	0.5	-	-	-	-	-
125	0.625	-	-	-	-	-
150	0.75	-	-	-	-	-
SF	-	-	-	-	-	-

	Torque, Lb-Ft	% Full Load Torque	Speed, RPM	Current Amps.
Locked Rotor Torque	2.36979	3.15	-	5.8349
Pull Up Torque	2.28703	3.04	-	-
Breakdown Torque	2.85879	3.8	-	-
Full Load	0.752313	100.0	-	0.83

Speed Torque Curve

Please contact Techtop for image.

Dimensional Drawing

Please contact Techtop for image.

Dimensions are for reference only. Allowance should be made for minor deviations in non standard specified properties.

3D Image Link: Not available for this motor

Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techttopind.com