



Three Phase Open Enclosure

NEMA

MOTOR MODEL:	GR3-CI-OP-365TC-4-BR-D-75
FACTORY TYPE:	-

NEMA Cast Iron, ODP

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	75.0	-
Speed, RPM	1775	1465
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	170.8/85.4	-
Power Factor	0.87	-
Nominal Efficiency	95.0	-
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
KVA Code	F	F
FL Amps. @ 208 V	188.9	-
LRC @ 60Hz HV	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	12	
Connection	4D/2D	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	94.75	0.8225
75%	94.8	0.879
100%	95.0	0.87
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	70.0	-
3D Image Link		
Not available for this motor		

GENERAL DATA	
Frame Size	365TC
Frame Enclosure	ODP
Mounting	Rigid
Insulation Class	F
Duty	Cont. / S1
NEMA Design	-
Frame Material	Cast Iron
Ingress Protection	23
Tropicalization	true
Cable Entry	-
Feet Removable	-
Double Drilled	-
Paint Color	Graphite Gray
Paint RAL	7024
Weight lb	959.84
MECHANICAL DATA	
DE Bearing	6313C3
NDE Bearing	6312C3
dB No-Load	-
Rotor Wk ² , Lb-Ft ²	-
Comp Ring (wavey washer)	-
TORQUE VALUES	
Torque lb-ft	% FLT
Locked Rotor Torque	-
Pull-Up Torque	-
Breakdown Torque	-
Full Load Torque	-
SITE CONDITIONS	
Ambient Temp °C	-
Altitude Above Sea Level m	-

*This report valid for above Date Code and newer models, please contact Techtop for more info.




Three Phase Open Enclosure

NEMA

MOTOR MODEL:	GR3-CI-OP-365TC-4-BR-D-75
FACTORY TYPE:	-

NEMA Cast Iron, ODP



Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techttopind.com



MOTOR MODEL:	GR3-CI-OP-365TC-4-BR-D-75
FACTORY TYPE:	-

NEMA

NEMA Cast Iron, ODP

