



IE3

IEC

<b>MOTOR MODEL:</b>	GR3-CI-TF-225MB3-2-BR-D-60
<b>FACTORY TYPE:</b>	TCX

## IE3 IEC Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	60.0	60.0
Speed, RPM	3560	2940
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	135.0/67.5	162.4/81.2
Power Factor	0.89	-
Nominal Efficiency	93.6	-
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
KVA Code	H	E
FL Amps. @ 208 V	-	-
LRC @ 60Hz HV	718.468	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	12	
Connection	DD/D	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	90.17	0.79
75%	92.28	0.87
100%	93.07	0.89
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	56.0	69.0
3D Image Link		
<a href="#">GR3-CI-TF-225MB3-2-BR-D-60</a>		

GENERAL DATA				
Frame Size	225M			
Frame Enclosure	TEFC			
Mounting	B3			
Insulation Class	F			
Duty	Cont. / S1			
NEMA Design	A			
Frame Material	Cast Iron			
Ingress Protection	55			
Tropicalization	true			
Cable Entry	2-M50X1.5			
Feet Removable	true			
Double Drilled	-			
Paint Color	Graphite Gray			
Paint RAL	7024			
Weight lb	767.0			
MECHANICAL DATA				
DE Bearing	6313C3			
NDE Bearing	6313C3			
dB No-Load	-			
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	-			
Comp Ring (wavy washer)	DE			
TORQUE VALUES			Torque lb-ft	% FLT
Locked Rotor Torque	382.352	432.0		
Pull-Up Torque	151.348	171.0		
Breakdown Torque	318.627	360.0		
Full Load Torque	88.5075	100.0		
SITE CONDITIONS				
Ambient Temp °C	40			
Altitude Above Sea Level m	1000			

\*This report valid for above Date Code and newer models, please contact Techttop for more info.




IE3

IEC

<b>MOTOR MODEL:</b>	GR3-CI-TF-225MB3-2-BR-D-60
<b>FACTORY TYPE:</b>	TCX

IE3 IEC Cast Iron, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	382.352	432.0	Start Configuration
Pull-Up Torque	151.348	171.0	Starting Current (A)
Breakdown Torque	318.627	360.0	No-Load Current (A)
Full Load	88.5075	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	21.45	-	-	-	-
25	15.0	27.65	13.48	3593.7	83.47	0.61
50	30.0	39.47	24.95	3587.9	90.17	0.79
75	45.0	53.0	36.57	3581.7	92.28	0.87
100	60.0	67.84	48.35	3575.2	93.07	0.89
125	75.0	83.6	60.3	3568.4	93.29	0.91

Techtop Industries  
 2815 Colonnades Court  
 Peachtree Corners, GA 30071  
 Tel: 678-436-5540  
 E-Mail: info@techttopind.com