



IE3

IEC

MOTOR MODEL:	GR3-CI-TF-225MB35-4-BR-D-60
FACTORY TYPE:	TCX

IE3 IEC Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	60.0	60.0
Speed, RPM	1775	1465
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	138.8/69.4	166.0/83.0
Power Factor	0.86	-
Nominal Efficiency	95.0	-
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
KVA Code	H	F
FL Amps. @ 208 V	-	-
LRC @ 60Hz HV	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	12	
Connection	DD/D	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	-	-
75%	-	-
100%	-	-
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	57.0	77.0
3D Image Link		
GR3-CI-TF-225MB35-4-BR-D-60		

GENERAL DATA				
Frame Size	225MB35			
Frame Enclosure	TEFC			
Mounting	B35			
Insulation Class	F			
Duty	Cont. / S1			
NEMA Design	-			
Frame Material	Cast Iron			
Ingress Protection	55			
Tropicalization	true			
Cable Entry	2-M50X1.5			
Feet Removable	true			
Double Drilled	-			
Paint Color	Graphite Gray			
Paint RAL	7024			
Weight lb	831.0			
MECHANICAL DATA				
DE Bearing	6313C3			
NDE Bearing	6313C3			
dB No-Load	-			
Rotor Wk ² , Lb-Ft ²	-			
Comp Ring (wavey washer)	-			
TORQUE VALUES			Torque lb-ft	% FLT
Locked Rotor Torque	-	-	-	-
Pull-Up Torque	-	-	-	-
Breakdown Torque	-	-	-	-
Full Load Torque	-	-	-	-
SITE CONDITIONS				
Ambient Temp °C	40			
Altitude Above Sea Level m	1000			

*This report valid for above Date Code and newer models, please contact Techttop for more info.

Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techttopind.com