



NEMA Premium

**NEMA**

|                      |                          |
|----------------------|--------------------------|
| <b>MOTOR MODEL:</b>  | GR3-CI-TF-326T-6-BR-F-30 |
| <b>FACTORY TYPE:</b> | TXC                      |

Premium NEMA Cast Iron, TEFC

| ELECTRICAL DATA                          |              |       |
|--|--------------|-------|
|  | 60 Hz        | 50 Hz |
| Horsepower                               | 30.0         | 30.0  |
| Speed, RPM                               | 1180         | -     |
| Voltage                                  | 575          | -     |
| # Phase                                  | 3            |       |
| Full Load Amps                           | 29.11190124  | -     |
| Power Factor                             | 0.82         | -     |
| Nominal Efficiency                       | 93.0         | -     |
| 3/4 Load Efficiency                      | -            | -     |
| Service Factor                           | 1.25         | 1.0   |
| KVA Code                                 | M            | -     |
| FL Amps. @ 208 V                         | -            | -     |
| LRC @ 60Hz HV                            | 325.901      | -     |
| Start Capacitor                          | -            |       |
| Start Capacitor V                        | -            |       |
| Run Capacitor                            | -            |       |
| Run Capacitor V                          | -            |       |
| Number of Leads                          | 6            |       |
| Connection                               | D            |       |
| Coil Resistance                          | -            |       |
| Date Code                                | -            |       |
|  |              |       |
| Load                                     | Efficiency % | P.F.  |
| 50%                                      | 92.38        | 0.65  |
| 75%                                      | 93.22        | 0.76  |
| 100%                                     | 93.12        | 0.81  |
|  |              |       |
| FULL LOAD TEMPERATURE RISE               |              |       |
| FL Temp Rise °C                          | 63.0         | -     |
|  |              |       |
| 3D Image Link                            |              |       |
| <a href="#">GR3-CI-TF-326T-6-BR-F-30</a> |              |       |

| GENERAL DATA                               |               |       |
|--|---------------|-------|
| Frame Size                                 | 326T          |       |
| Frame Enclosure                            | TEFC          |       |
| Mounting                                   | Rigid         |       |
| Insulation Class                           | F             |       |
| Duty                                       | Cont. / S1    |       |
| NEMA Design                                | A             |       |
| Frame Material                             | Cast Iron     |       |
| Ingress Protection                         | 55            |       |
| Tropicalization                            | true          |       |
| Cable Entry                                | 1-NPT 2"      |       |
| Feet Removable                             | true          |       |
| Double Drilled                             | true          |       |
| Paint Color                                | Graphite Gray |       |
| Paint RAL                                  | 7024          |       |
| Weight lb                                  | 648.27        |       |
|  |               |       |
| MECHANICAL DATA                            |               |       |
| DE Bearing                                 | 6312C3        |       |
| NDE Bearing                                | 6312C3        |       |
| dB No-Load                                 | -             |       |
| Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup> | -             |       |
| Comp Ring (wavy washer)                    | DE            |       |
|  |               |       |
| TORQUE VALUES                              |               |       |
|  | Torque lb-ft  | % FLT |
| Locked Rotor Torque                        | 406.285       | 302.0 |
| Pull-Up Torque                             | 216.595       | 161.0 |
| Breakdown Torque                           | 495.075       | 368.0 |
| Full Load Torque                           | 134.531       | 100.0 |
|  |               |       |
| SITE CONDITIONS                            |               |       |
| Ambient Temp °C                            | 40            |       |
| Altitude Above Sea Level m                 | 1000          |       |

\*This report valid for above Date Code and newer models, please contact Techtop for more info.




NEMA Premium

**NEMA**

|                      |                          |
|----------------------|--------------------------|
| <b>MOTOR MODEL:</b>  | GR3-CI-TF-326T-6-BR-F-30 |
| <b>FACTORY TYPE:</b> | TXC                      |

Premium NEMA Cast Iron, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

| Torque Values       | Torque lb-ft | % FLT | Performance Values   |
|---------------------|--------------|-------|----------------------|
| Locked Rotor Torque | 406.285      | 302.0 | Start Configuration  |
| Pull-Up Torque      | 216.595      | 161.0 | Starting Current (A) |
| Breakdown Torque    | 495.075      | 368.0 | No-Load Current (A)  |
| Full Load           | 134.531      | 100.0 | No-Load Power Factor |

| % Load | Horsepower | Current, Amps | Input power, Kilowatts | Speed, RPM | Efficiency | PF   |
|--------|------------|---------------|------------------------|------------|------------|------|
| 0      | -          | 17.02         | -                      | -          | -          | -    |
| 25     | 7.5        | 18.23         | 6.31                   | 1196.0     | 88.29      | 0.43 |
| 50     | 15.0       | 23.42         | 12.07                  | 1192.5     | 92.38      | 0.65 |
| 75     | 22.5       | 29.7          | 17.94                  | 1188.6     | 93.22      | 0.76 |
| 100    | 30.0       | 36.9          | 23.95                  | 1184.5     | 93.12      | 0.81 |
| 125    | 37.5       | 44.85         | 30.1                   | 1179.9     | 92.6       | 0.84 |

Techtop Industries  
 2815 Colonnades Court  
 Peachtree Corners, GA 30071  
 Tel: 678-436-5540  
 E-Mail: info@techttopind.com