



Pump Motors

NEMA

MOTOR MODEL:	GR3-CI-TF-364JP-2-BR-D-60
FACTORY TYPE:	TXC

Premium NEMA Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	60.0	60.0
Speed, RPM	3560	2940
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	136.41/68.2	162.4/81.2
Power Factor	0.89	-
Nominal Efficiency	93.6	91.2
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
KVA Code	L	E
FL Amps. @ 208 V	-	-
LRC @ 60Hz HV	718.468	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	12	
Connection	DD/D	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	90.17	0.79
75%	92.28	0.87
100%	93.07	0.89
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	49.0	-
3D Image Link		
Not available for this motor		

GENERAL DATA		
Frame Size	364JP	
Frame Enclosure	TEFC	
Mounting	Rigid	
Insulation Class	F	
Duty	Cont. / S1	
NEMA Design	A	
Frame Material	Cast Iron	
Ingress Protection	55	
Tropicalization	true	
Cable Entry	1-NPT 2"	
Feet Removable	-	
Double Drilled	-	
Paint Color	Graphite Gray	
Paint RAL	7024	
Weight lb	761.828	
MECHANICAL DATA		
DE Bearing	6313C3	
NDE Bearing	6313C3	
dB No-Load	-	
Rotor Wk ² , Lb-Ft ²	-	
Comp Ring (wavy washer)	NDE	
TORQUE VALUES		% FLT
Locked Rotor Torque	382.352	432.0
Pull-Up Torque	151.348	171.0
Breakdown Torque	318.627	360.0
Full Load Torque	88.5075	100.0
SITE CONDITIONS		
Ambient Temp °C	40	
Altitude Above Sea Level m	1000	

*This report valid for above Date Code and newer models, please contact Techttop for more info.




Pump Motors

NEMA

MOTOR MODEL:	GR3-CI-TF-364JP-2-BR-D-60
FACTORY TYPE:	TXC

Premium NEMA Cast Iron, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	382.352	432.0	Start Configuration
Pull-Up Torque	151.348	171.0	Starting Current (A)
Breakdown Torque	318.627	360.0	No-Load Current (A)
Full Load	88.5075	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	21.45	-	-	-	-
25	15.0	27.65	13.48	3593.7	83.47	0.61
50	30.0	39.47	24.95	3587.9	90.17	0.79
75	45.0	53.0	36.57	3581.7	92.28	0.87
100	60.0	67.84	48.35	3575.2	93.07	0.89
125	75.0	83.6	60.3	3568.4	93.29	0.91

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com