

## Techtop Industries Nameplate and Performance Data

NAMEPLATE DATA		
	60 Hz.	50 Hz.
Horsepower	125.0	125.0
Frame Size	444TSC	
Speed, RPM	3575	2960
Voltage	3 Phase US	380
# Phase	3	
Full Load Amps	136.8876496	166
Power Factor	0.9	-
Nominal Efficiency	95.0	93.5
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
Duty	Cont. / S1	
FL Temp Rise °C	81.0	-
Enclosure	TEFC	
Ambient Temp °C	40	
KVA Code	M	E
FL Amps. @ 208 V	-	-
Insulation Class	F	
NEMA Design	A	
Weight	1437.66	
DE Bearing	6316C3	
NDE Bearing	6316C3	
dB No-Load	-	
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	-	
Start Capacitor		
Start Capacitor V	-	
Run Capacitor		
Run Capacitor V	-	
Number of Leads	6	
Connection	?	
Coil Resistance	0.049765	

Motor Model:	GR3-CI-TF-444TSC-2-BR-E-125
--------------	-----------------------------

Performance Load Values:

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	62.5	37.85	-	-	-	-
25	62.5	54.82	30.04	3594.5	89.21	0.89
50	62.5	84.97	57.36	3589.2	93.44	0.85
75	93.75	118.4	85.03	3583.6	94.56	0.9
100	125.0	154.45	113.07	3577.7	94.81	0.92
125	62.5	192.43	141.52	3571.6	94.69	0.92
150	62.5	231.66	170.39	3565.2	94.37	0.92
SF	-	-	-	-	-	-

	Torque, Lb-Ft	% Full Load Torque	Speed, RPM	Current Amps.
Locked Rotor Torque	693.434	330.0	-	1081.0
Pull Up Torque	310.995	148.0	-	-
Breakdown Torque	821.614	391.0	-	-
Full Load	210.131	100.0	3581.8	154.4

### Speed Torque Curve

Please contact Techttop for image.

### Dimensional Drawing

**DRAWING UNAVAILABLE CONTACT TECHTOP**

Dimensions are for reference only. Allowance should be made for minor deviations in non standard specified properties.

3D Image Link: Not available for this motor

Techtop Industries  
2815 Colonnades Court  
Peachtree Corners, GA 30071  
Tel: 678-436-5540  
E-Mail: info@techttopind.com