NEMA Premium

NEMA

MOTOR MODEL:	OX3-CI-TF-449T-6-RR-E-200
FACTORY TYPE:	TXC

Premium NEMA Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	200.0	200.0
Speed, RPM	1180	980
Voltage	460	380
# Phase	3	
Full Load Amps	224.6806142	277
Power Factor	0.87	-
Nominal Efficiency	95.8	94.0
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
KVA Code	H	E
FL Amps. @ 208 V	-	-
LRC @ 60Hz HV	2045.8	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	6	
Connection	D	
Coil Resistance	-	
Date Code	-	
Load	**Efficiency %**	**P.F.**
50%	94.92	0.76
75%	95.26	0.84
100%	94.97	0.86
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	113.0	-
3D Image Link		
OX3-CI-TF-449T-6-RR-E-200		

*This report valid for above Date Code and newer models, please contact Techtop for more info.

GENERAL DATA	
Frame Size	449T
Frame Enclosure	TEFC
Mounting	Rigid
Insulation Class	F
Duty	Cont. / S1
NEMA Design	C
Frame Material	Cast Iron
Ingress Protection	55
Tropicalization	true
Cable Entry	2-NPT 3"
Feet Removable	-
Double Drilled	true
Paint Color	Graphite Gray
Paint RAL	7024
Weight lb	2244.69
MECHANICAL DATA	
DE Bearing	NU319
NDE Bearing	6319C3
dB No-Load	-
Rotor Wk², Lb-Ft²	-
Comp Ring (wavey washer)	None

TORQUE VALUES	Torque lb-ft	% FLT
Locked Rotor Torque	2467.2	241.0
Pull-Up Torque	-	-
Breakdown Torque	3030.26	296.0
Full Load Torque	1023.74	100.0
SITE CONDITIONS		
Ambient Temp °C	40	
Altitude Above Sea Level m	1000	

Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techtopind.com