

## Techtop Industries Nameplate and Performance Data

NAMEPLATE DATA		
	60 Hz.	50 Hz.
Horsepower	7.5	-
Frame Size	213TZ	
Speed, RPM	1740	-
Voltage	1 Phase US	-
# Phase	1	
Full Load Amps	34.3-31.0	-
Power Factor	0.94	-
Nominal Efficiency	82.0	-
3/4 Load Efficiency	-	-
Service Factor	1.15	-
Duty	Cont. / S1	
FL Temp Rise °C	-	-
Enclosure	TEFC	
Ambient Temp °C	40	
KVA Code	H	-
FL Amps. @ 208 V	34.3	-
Insulation Class	F	
NEMA Design	L	
Weight	185.0	
DE Bearing	6208-2RZ	
NDE Bearing	6206-2RZ	
dB No-Load	-	
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	-	
Start Capacitor		
Start Capacitor V	350	
Run Capacitor		
Run Capacitor V	450	
Number of Leads	5	
Connection	-	
Coil Resistance	0.0	

<b>Motor Model:</b>	<b>RD1-RS-TF-213TZ-4-B-B-7.5</b>
---------------------	----------------------------------

Performance Load Values:


% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-
150	-	-	-	-	-	-
SF	-	-	-	-	-	-

	Torque, Lb-Ft	% Full Load Torque	Speed, RPM	Current Amps.
Locked Rotor Torque	89.8351	400.0	-	687.0
Pull Up Torque	48.2864	215.0	-	-
Breakdown Torque	53.901	240.0	-	-
Full Load	22.4588	100.0	-	31.79

### Speed Torque Curve

Please contact Techtop for image.

### Dimensional Drawing



Dimensions are for reference only. Allowance should be made for minor deviations in non standard specified properties.

3D Image Link: Not available for this motor